

SURE STAR R4S-400G1V2

400 Watt EPS Power Supply Mini Redundant

Manufacturer-Item-No. 2215

EAN 4250273422153



SURE STAR R4S-400G1V2

400 Watt EPS Power Supply Mini Redundant

Suitable for permanent use 24 hours / 7 days. Hot Swap exchange of modules possible during operation. This ensures trouble-free use. Separate power inputs. The power supply can also be used on standard ATX motherboards.

- 400 Watts
- Mini Redundant
- High Efficiency
- Low Noise
- 4U
- 4× fan
- Hot Swap



SURE STAR R4S-400G1V2

400 Watt EPS Power Supply Mini Redundant

Manufacturer-Item-No. 2215

EAN 4250273422153



Technical Data

Features

- 400 Watts
- Mini Redundant
- High Efficiency
- Low Noise
- 4U
- 4× fan
- Hot Swap

Special Features

- Active power factor correction
- Overload protection
- Overvoltage protection
- Short circuit protection
- Working temperature: 0 °C ~ 50°C
- Storage temperature: -20°C ~ 70°C
- altitude during operation: 5000m
- Safety: UL, TUV, CB, CE, FCC, BSMI, CCC. (Class B)
- WEEE Directive (2002/96/EC)
- RoHS COMPLIANT

Power

- 400 Watts

Input Current

- Full range
- 115V ~ 230V, 47Hz ~ 63Hz
- Dual AC IN

Output Current

Voltage	+3.3V	+5V	+12V	-12V	+5VSB
Current (max)	25A	25A	33A	0,8A	3,5A
Current (min)	1A	1A	1A	0A	0.5A
interference voltage (P-P)	60mVp-p	60mVp-p	120mVp-p	120mVp-p	60mVp-p

Formfaktor

- 4 U

Included Supply

- Brackets

Logistic data

- Article Measurements
150 x 174 x 86 mm (W x D x H)
- Packaging Unit Measurements
310 x 450 x 200 mm (W x D x H)
- Net Weight Article (total)
8,0 kg
- Gross Weight Packaging Unit
20,0 kg
- Packaging Unit
2 Pcs. per Carton
- Country of Origin
China