

FANTEC MR-SA1262-12G/6G

SAS 12G + SATA 6G backplane for 6×2.5" HDD/SSD

Manufacturer-Item-No. 2194

EAN 4250273421941



FANTEC MR-SA1262-12G

SAS 12G + SATA 6G Backplane for 6×2,5" HDD/SSD

SAS I,II,III 12G + SATA I,II,III 6G backplane for 6x 2.5" HDD or SSD (max. height 9.5mm) in a 5.25" bay. With a 40mm fan at the back. Harddisk tray. Metal case in gray, front metal in black.

- 1x 5.25 slot for 6× 2.5" HDD(SSD)
- For SAS 12G or SATA 6G (SATA 3.2 & 3.3) HDD
- For SAS I/II/III or SATA I/II/III HDDs and SSDs
- For 2.5" HDDs or SSD up to 9.5mm height
- LED for power and HDD access
- Quick mounting and changing of hard disks by hard disk carrier
- Suitable for SAS up to 12G (SAS III)
- Suitable for SATA up to 6G
- For 2.5" SATA/SAS SSD and hard disks
- Suitable for RAID
- Plug & Play
- Hotswap
- Hard disk trays individually lockable
- Anti-vibration suspension on the trays
- LED for status indication



FANTEC MR-SA1262-12G/6G

SAS 12G + SATA 6G backplane for 6×2.5" HDD/SSD

Manufacturer-Item-No. 2194

EAN 4250273421941



Technical Data

Features

- 1x 5.25 slot for 6× 2.5" HDD(SSD)
- For SAS 12G or SATA 6G (SATA 3.2 & 3.3) HDD
- For 2.5" HDD or SSD up to 9,5mm height
- LED for power and HDD access*
- (*Green: Power on. *Orange flashing: HDD access)
- Quick mounting and changing of hard disks by hard disk carrier
- Suitable for SAS up to 12G (SAS III)
- Suitable for SATA up to 6G (SATA 3.2&3.3)
- Suitable for RAID
- Plug & Play
- Hotswap
- Hard drive tray can be locked individually
- Anti-vibration springing on the trays
- LED for status indication

Special Features

- maximum height of individual data carriers 9.5mm
- LED for status indication:
Green - on
flashing orange - data access
- 1x 40x40x20mm fan
- front door with ventilation holes
- Form factor 1x 5.25" bay
- Enclosure, bays and front doors made of metal
- case gray, bays silver-gray, front doors black
- optional connector for sensor kit prepared
- for the use of SAS 12G we recommend cables of type miniSAS SFF-8643

Interfaces

- 1x SATA 15-pin external power supply

Data Interfaces

- SAS I / II / III 12G + SATA I / II / III 6G

Power Supply

- 1x SATA 15-pin external power supply

Form Factor

- 1 × 5.25 "

Included Supply

- Screws

Logistic data

- **Article Measurements**
149.8 × 159 × 41.6 mm (W × D × H)
- **Retail Box Measurements**
150 × 195 × 47 mm (W × D × H)
- **Packaging Unit Measurements**
× × mm (W × D × H)
- **Net Weight Article (total)**
1,09 kg
- **Gross Weight Packaging Unit**
kg
- **Packaging Unit**
Pcs. per Carton
- **Country of Origin**
China